## Surround Loudspeaker



## VS-14

With great looks and advanced technology, the Icon V Series VS-14 surround speaker serves up enveloping cinema-style sound that definitely brings a new dimension of reality and convenience to home theater.

The VS-14 employs a 4.5" fiber-composite woofer cone that is lightweight, yet powerful. Not only does this reliable low-frequency component create improved tonal balance and imaging, it also generates amazing dynamics and deep bass.

Even more remarkable is the VS-14's all-new, patent-pending Tractrix® Horn-loaded tweeters with XT technology. This proprietary design equalizes the speed of sound waves from the horns and smoothes the dispersion pattern.

Furthermore, the exclusive Wide Dispersion Surround Technology, or WDST, that's tied in with the tweeters and horns allows the VS-14 to create a smooth, high dispersion pattern, providing crystal clear sonic detail even in listening areas with less than ideal configurations. So, no matter where you sit, this surround speaker promises to draw you into the middle of the action.

The speaker's sleek, black cabinet has a stylish look that complements modern video and audio components. And, with the furniture-grade finish on the top and bottom caps, it will look great in any room.

- Patent-pending XT Tractrix<sup>®</sup> Horns with wide dispersion technology
- Dual tweeters create precise high frequencies
- High-output woofer generates hard-hitting lows
- High-style, contemporary black cabinet fits any décor
- Fixed grille protects drivers
- Easy to drive with typical A/V receiver

## **SPECIFICATIONS**

low frequency extension  power handling  50 W continuous, 200 W peak  sensitivity  89dB  nominal impedance  8 ohms compatible  crossover frequency  drive components  Two-way system utilizing one 4.5" fiber-composite lightweight cone woofer and two 1" aluminum dome tweeters mounted in dual 4.5" square 90° X 90° XT Tractrix® horns in a WDST configuration  enclosure material  MDF (medium density fiberboard)  enclosure type  Sealed enclosure height  6.75" (17.1 cm)  width  15" (38.1 cm)  depth  6.5" (16.5 cm)  weight  7.5 lbs (3.4 kg)  finishes  Black vinyl with furniture-grade black wood veneer top and bottom cap	frequency response	99Hz - 23kHz +/- 3dB
sensitivity  89dB  nominal impedance  8 ohms compatible  crossover frequency  2000Hz  drive components  Two-way system utilizing one 4.5" fiber-composite lightweight cone woofer and two 1" aluminum dome tweeters mounted in dual 4.5" square 90° X 90° XT Tractrix® horns in a WDST configuration  enclosure material  MDF (medium density fiberboard)  enclosure type  Sealed enclosure  height  6.75" (17.1 cm)  width  15" (38.1 cm)  depth  6.5" (16.5 cm)  weight  7.5 lbs (3.4 kg)  finishes	low frequency extension	92Hz
nominal impedance 8 ohms compatible  crossover frequency 2000Hz  drive components Two-way system utilizing one 4.5" fiber-composite lightweight cone woofer and two 1" aluminum dome tweeters mounted in dual 4.5" square 90° X 90° XT Tractrix® horns in a WDST configuration  enclosure material MDF (medium density fiberboard)  enclosure type Sealed enclosure  height 6.75" (17.1 cm)  width 15" (38.1 cm)  depth 6.5" (16.5 cm)  weight 7.5 lbs (3.4 kg)  finishes Black vinyl with furniture-grade black	power handling	50 W continuous, 200 W peak
crossover frequency  drive components  Two-way system utilizing one 4.5" fiber-composite lightweight cone woofer and two 1" aluminum dome tweeters mounted in dual 4.5" square 90° X 90° XT Tractrix® horns in a WDST configuration  enclosure material  MDF (medium density fiberboard) enclosure type  Sealed enclosure height  6.75" (17.1 cm)  width  15" (38.1 cm)  depth  6.5" (16.5 cm)  weight  7.5 lbs (3.4 kg)  finishes  Black vinyl with furniture-grade black	sensitivity	89dB
drive components  Two-way system utilizing one 4.5" fiber-composite lightweight cone woofer and two 1" aluminum dome tweeters mounted in dual 4.5" square 90° X 90° XT Tractrix® horns in a WDST configuration  enclosure material  MDF (medium density fiberboard) enclosure type  Sealed enclosure height  6.75" (17.1 cm) width  15" (38.1 cm)  depth  6.5" (16.5 cm)  weight  7.5 lbs (3.4 kg)  finishes  Black vinyl with furniture-grade black	nominal impedance	8 ohms compatible
fiber-composite lightweight cone woofer and two 1" aluminum dome tweeters mounted in dual 4.5" square 90° X 90° XT Tractrix® horns in a WDST configuration  enclosure material  MDF (medium density fiberboard) enclosure type  Sealed enclosure height  6.75" (17.1 cm)  width  15" (38.1 cm)  depth  6.5" (16.5 cm)  weight  7.5 lbs (3.4 kg)  finishes  Black vinyl with furniture-grade black	crossover frequency	2000Hz
enclosure type  height  6.75" (17.1 cm)  width  15" (38.1 cm)  depth  6.5" (16.5 cm)  weight  7.5 lbs (3.4 kg)  finishes  Black vinyl with furniture-grade black	drive components	fiber-composite lightweight cone woofer and two 1" aluminum dome tweeters mounted in dual 4.5" square 90° X 90° XT Tractrix®
height 6.75" (17.1 cm)  width 15" (38.1 cm)  depth 6.5" (16.5 cm)  weight 7.5 lbs (3.4 kg)  finishes Black vinyl with furniture-grade black	enclosure material	MDF (medium density fiberboard)
width 15" (38.1 cm)  depth 6.5" (16.5 cm)  weight 7.5 lbs (3.4 kg)  finishes Black vinyl with furniture-grade black	enclosure type	Sealed enclosure
depth 6.5" (16.5 cm)  weight 7.5 lbs (3.4 kg)  finishes Black vinyl with furniture-grade black	height	6.75" (17.1 cm)
weight 7.5 lbs (3.4 kg) finishes Black vinyl with furniture-grade black	width	15" (38.1 cm)
finishes Black vinyl with furniture-grade black	depth	6.5" (16.5 cm)
, , , , , , , , , , , , , , , , , , ,	weight	7.5 lbs (3.4 kg)
	finishes	Black vinyl with furniture-grade black wood veneer top and bottom cap

